



WPSAN235140AA

ENERGY ABSORBING LANYARDS

Fall protection



Specific benefits



Ease of Use

-
-
-



Sustainability

-
-
-

Applications

- Public Works
- Others

Certifications and norms

Risk Protection



Fall



WPSAN235140AA

ENERGY ABSORBING LANYARDS

Fall protection

Standards - Details

Technical details

Type of equipment	Energy-absorbing lanyard made of tubular webbing
Composition of the main support	Galvanized steel, Polyamide, Polyester, Polyethylene
Max. length (m)	1,40
Strap width (mm)	35
Min. length (m)	1,40
Length (m)	1,40
Gate opening (mm)	18
Opening (inch)	0.7074
Color	Orange
Weight (kg)	0,790
Type of conditioning	Box of 5
Fall arrest work situations	Vertical movement on a permanent structure, Work positioning, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	1,40



WPSAN235140AA

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WPSAN235140AA	Orange	2 m	WPSAN235140AA	3295249309480	13295249309487	5	1	8.85 kg	39.0 cm	43.0 cm	18.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height