Hand protection

VENICUTDX0

LONG-LASTING CUT WORK

Level D cut-resistant glove, contact heat resistant up to 250°, ideal for intensive work



Specific benefits

Performance

· The high-performance HEATnocut fiber provides excellent abrasion and cut resistance

· The high-performance HEATnocut fiber provides resistance to contact heat (250° for 15 seconds)

Applications

- **Public Works**
- **Building**
- **Mining**

Certifications and norms

CATEGORY II

EN 388
4 X 4 2 D

EN 407
X 2 X X X X

A4 X X

Risk Protection

Cutting

Wearing

DELTAPLUS

enjoy safety.

Edit 19/11/2026
www.deltaplus-usa.com

Hand protection

VENICUTDX0

LONG-LASTING CUT WORK

Level D cut-resistant glove, contact heat resistant up to 250°, ideal for intensive work

Standards - Details

EN388:2016+A1:2018
4 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997

EN 407
X [0-4] BURNING BEHAVIOUR
2 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Knitted uncoated glove with leather palm
Mechanical Glove Type	Tricot
Special gloves kind	Knitted with palm leather
Fiber	HEATnocut, PEHD
Gauge	10
Benefits element	Reach, Vendor pack
Color	Yellow-Grey
Size	9, 10
Type of conditioning	in individual bag

Packaging

Sale unit: in individual bag
60 pairs /box



手部防护

202012

长时间正常切割作业

D 级防割手套，接触耐热高达 250°，是高强度工作的理想选择

物流信息

产品代码	颜色	尺码	六位码	条形码	箱码			重量			
VECUTDX0GJ09	黄色-灰色	09	202012	3295249157289	13295249157286	60	12	10.2 kg	28.0 cm	35.0 cm	37.0 cm
VECUTDX0GJ10	黄色-灰色	10	202012	3295249157296	13295249157293	60	12	11.3 kg	28.0 cm	35.0 cm	37.0 cm

箱规

最低销售

箱长

箱宽

箱高