



Protección anticaídas

TRA22

ANTICAÍDAS Y SALVAMENTO, ESPACIOS CONFINADOS

Trípode de aluminio de hasta 2 metros, con 2 pletinas de soporte, ligero y fácil de instalar para todo tipo de trabajos en espacios reducidos



Aplicaciones

- Edificación
- Reformas / Profesional autónomo
- Mantenimiento
- Industria química
- Petróleo y gas (extracción)
- Industria minera

Certificaciones y normas



EN 795
TIPO B

TS16415
3

Protección contra



Caídas



Protección anticaídas

TRA22

ANTICAÍDAS Y SALVAMENTO, ESPACIOS CONFINADOS

Trípode de aluminio de hasta 2 metros, con 2 pletinas de soporte, ligero y fácil de instalar para todo tipo de trabajos en espacios reducidos

Detalles - Normas

Detalles técnicos

Tipo de equipamiento	Trípode telescópico
Dispositivo de anclaje	Trípode
Composición del soporte principal	Aluminio
Longitud máxima (m)	1,97
Longitud mínima (m)	1,25
Color	Aluminio
Peso (kg) (kg)	17,4
Resistencia (Kn)	20
Distancia hasta el suelo (m)	1,89
No incluido	Marcha TRA103
Situaciones de trabajo anticaídas	Salvamento y evacuación, Desplazamiento vertical, espacio confinado



Fall protection

TRA22

FALL ARREST AND RESCUE, CONFINED SPACE

Aluminium tripod up to 2 metres, with 2 support plates, light and easy to install for all types of work in confined spaces

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TRA22	Aluminium-coloured	Adjustable	TRA22	3295249194093	13295249194090	1	1	23.75 kg	150.5 cm	30.5 cm	28.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height